

on said first edge, said first and second connecting means making said first and second work surfaces coplanar,

(c) a table extension insert plate having a table extension wing plate opening, a third work surface and third connecting means, and fourth connecting means in said table extension rectangular opening for removably attaching said table extension insert plate to said table extension, said third and fourth connecting means making said second and third work surfaces coplanar,

(d) a power tool having a cutting element, said power tool having attachment means for attaching said power tool to the bottom of said table extension insert plate, and adjustment means for vertically adjusting the position of said power tool in relation to said table extension insert plate, and

(e) an opening in said table extension insert plate through which said power tool cutting element may extend,

whereby a user may use said power tool attachment in sequence with said table saw, without having to remove or replace said saw or power tool, and may adjust said power tool vertically to achieve a desired depth of cut in a workpiece, or to lower said power tool completely below said second work area.

2. The combination according to claim 1, wherein said power tool is a dado attachment comprising:

(a) said cutting element comprising at least one dado blade mounted on a blade shaft, said shaft extending through an adjustment and bearing housing,

(b) adjustment means of said adjustment and bearing housing whereby said shaft may be vertically adjusted, such that said at least one dado blade may extend above said second work area an adjustment range of zero inches to at least 3/4 inch,

- (c) an electric motor and a mounting bracket, said mounting bracket supporting said electric motor and having said attachment means for attaching said power tool to said table extension insert plate,
- (d) stabilizing means of said mounting bracket, said blade shaft
5 extending through said stabilizing means, said stabilizing means permitting vertical adjustment of said blade shaft and said at least one dado blade, throughout said adjustment range, and
- (e) power transmission means whereby rotation of said motor causes rotation of said blade shaft, throughout said adjustment range of said
10 blade shaft and said at least one dado blade, and
3. The combination according to claim 2, wherein said adjustment means comprises an adjustment screw extending to an adjustment port in said table extension insert plate, and extending through a threaded component of said adjustment and bearing housing.
- 15 4. The combination according to claim 2, wherein said power transmission means comprises a worm gear affixed to the shaft of said electric motor, a spur gear affixed to said blade shaft and engagement of said worm and spur gears.
5. The combination according to claim 3, wherein said power transmission means comprises a worm gear affixed to the shaft of said electric motor, a spur
20 gear affixed to said blade shaft and engagement of said worm and spur gears.
6. The combination according to claim 1, wherein an adjustable fence guide may be adjusted to desired distances from said saw blade or said cutting element, for guiding workpieces to said saw blade or said at least one dado blade.
- 25 7. The combination according to claim 2, wherein an adjustable fence guide may be adjusted to desired distances from said saw blade or said cutting element, for guiding workpieces to said saw blade or said at least one dado blade.
8. The combination according to claim 3, wherein an adjustable fence guide
30 may be adjusted to desired distances from said saw blade or said cutting

element, for guiding workpieces to said saw blade or said at least one dado blade.

9. The combination according to claim 4, wherein an adjustable fence guide may be adjusted to desired distances from said saw blade or said cutting
5 element, for guiding workpieces to said saw blade or said at least one dado blade..

10. The combination according to claim 5, wherein an adjustable fence guide may be adjusted to desired distances from said saw blade or said cutting
10 element, for guiding workpieces to said saw blade or said at least one dado blade..